

# DPU Series

DPU12 PRINTER

The DPU12 is a small, high-speed panel-mount line thermal printer unit.

Its self-contained design is a great fit for a wide range of applications where space is at a premium.

Designed for overall simplicity, everything is accessible from the front, including paper roll replacement.



DPU12

Offering these features and more, applications for the DPU12 are virtually limitless for providing hardcopy records wherever and whenever they are needed. Examples include measuring instruments such as data loggers, medical equipment, receipt, industrial control, ticket and tag printing, and small kiosk installations.

- Compact and light weight (approx. 290g tear bar model)
- High-speed printing (60mm/sec. max)
- Easy paper installation with auto loading function
- Easy fitting on the panel with one gap hole only
- 5V single power drive
- Available with tear bar or auto cutter (partial cut)

Model	DPU12-0FS / DPU12-1FS	
Printing Method	Thermal line dot system	
Printing width / Paper width	48 mm / 58 mm	
Dot configuration dots/line	384	
Dot resolution	8 dots/mm	
Printing speed (mm/s.)	Maximum 60	
Command	SII original	
Character set	Graphics character set KATAKANA (Japanese) characters KANJI (JIS 1 and 2 level) character set Download character User-defined character option font	
Character size	24 x 12 16 x 8	
Interface	RS-232C compatible	
Operating Temperature (°C) Environment range	0 to 50	
Storage Temperature (°C) Environment range	-10 to 50	
Dimensions (WxDxH) mm	105 x 120 x 73	
Weight g	Approx. 350	
Cut method	tear bar	auto-cutter (partial cut)